

ASI Technologies, Inc.



MK 85 SERIES

36 VOLT GEAR DRIVE SYSTEMS

The MK 85 incorporates high strength gearing in our standard die cast housing. Vehicle weights up to 1500 lbs and speeds up to 12 mph are possible due to the large ratio variations offered by this unique and compact drive system. Motor, electro-magnetic brake, harnessing, connectors, gear reduction and differential are included in one easy-to-install package. Detailed on this sheet are standard units. Other motors, voltages and ratios are available. Axle configurations are made to order, including hubs, if required. Please contact the factory for more information.




Unit type		MK 75	MK 75	MK 85	MK 85	MK 85
Option		1	2	3	4	5
Voltage		36	36	36	36	36
No Load Speed, RPM		500	300	175	105	65
Maximum continuous operating point (Motor Limited)						
Torque	In-Lbs.	192	310	580	970	1580
Speed	RPM	450	270	150	90	55
Current	Amps	40	40	40	40	40




ASI Technologies 209 Progress Dr., Montgomeryville, PA 18936
www.asidrives.com +1.215.661.1002 fax +1.215.661.1009

MK 50/60 SERIES GEAR DRIVE SYSTEM



NOTES

1. PREFERRED MOUNTING IS WITH MOTOR ON RIGHT SIDE LOOKING FORWARD.
2. MAX. ALLOWABLE GROSS VEHICLE WEIGHT IS DEPENDENT ON MAX SPEED, CONSULT FACTORY.
3. HOUSING MATERIAL IS DIE CAST ALUMINUM; AXLES ARE STEEL ALLOY.
4. WEIGHT OF TRANSAXLE IS 22.7 KG [50.0 LBS] WITH MOTOR AND BRAKE.
5. THIS GEARBOX IS SEALED AND LUBRICATED FOR LIFE. NO MAINTENANCE IS REQUIRED.
6. ESTIMATED GEARBOX EFFICIENCY GREATER THAN 95%
7. THE SUITABILITY OF THIS TRANSAXLE FOR A SPECIFIC APPLICATION IS THE RESPONSIBILITY OF THE PURCHASER.
8. EXCESSIVE ACCEL AND DECEL CAN ADVERSELY EFFECT THE LIFE AND INTEGRITY OF THE UNIT.



RESTRAINT SLEEVE



ASI TECHNOLOGIES INC
GEAR DRIVE SYSTEMS

209 Progress Drive
Montgomeryville, PA 18936 USA

Voice: +1.215.661.1002

Fax: +1.215.661.1009

www.asidrives.com